

**POWERdrive**

POWERdrive’s dynamic response can be tuned to fit any content - from exceptionally smooth fades in architecture to fast-paced video in entertainment. This constant current LED driver is DMX/RDM/DALI compatible, and allows you to create your colour or dynamic show without an external controller. Symbiosis ensures the LED driver works seamlessly together with LED modules, controls and intelligent luminaire elements.


**Product offering**



**POWERdrive 106/M-BIS**

Part number P/N	PWR106M1-BIS
Product description	POWERdrive, 100W, DMX/RDM/DALI, 4 control channels, constant current, 4x 57V outputs, long metal

**Order number configurator**



P/N	LED driver part number
-----	------------------------

**Warranty**

Warranty period	<a href="#">General Terms and Conditions</a>
-----------------	--

Project name:	Contact details:
Project number:	
LED driver order number:	

## Electrical specifications

Driver type	Constant current
Number of LED outputs	4
Maximum LED output power	100W
Programmable LED output current range	200 - 1050mA
LED output type	programmable in 10mA steps via DMX terminal and FluxTool
LED output voltage range	2 - 57V
Nominal input voltage range AC	120 - 277V
Nominal input voltage range DC	120 - 275V
Control protocol	DMX/RDM/DALI
Control channels	4

## Dimensions, weight, packaging

Length (L)	typical: 370 mm / 14.57 in
Width (W)	typical: 41 mm / 1.61 in
Height (H)	typical: 30 mm / 1.18 in
Weight	774 g
Products per box	20 pcs

## Certifications



### Europe, Rest of World

eldoLED B.V.  
Science Park Eindhoven 5125  
5692 ED Son  
The Netherlands

E: [info@eldoled.com](mailto:info@eldoled.com)  
W: [www.eldoled.com](http://www.eldoled.com)

### North America

eldoLED America  
One Lithonia Way  
Conyers, GA 30012  
USA

E: [info@eldoled.com](mailto:info@eldoled.com)  
W: [www.eldoled.com](http://www.eldoled.com)